



3752

Our Reference: ITT-229-D

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: David L. Noone, Frank L. Mitchell
and Peter Wenig

Serial No.: 09/995,213

Filing Date: November 26, 2001

Examiner/Group Art Unit: David L. Noone/3752

Title: MULTI-LAYER TUBING HAVING
ELECTROSTATIC DISSIPATION FOR
HANDLING HYDROCARBON FLUIDS

CERTIFICATE OF MAILING AND TRANSMITTAL LETTER

BOX NON-FEE AMENDMENT

Assistant Commissioner of Patents
Washington, D.C. 20231

Sir:

Transmitted with this document are a Postcard and Amendment in connection with the above-identified application.

X No additional fee is required.


X Please charge any deficiency or credit any excess in the enclosed fees to Deposit Account Number 25-0115.

I hereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to: Assistant Commissioner of Patents, Washington, D.C. 20231, on September 19, 2002.

Andrew R. Basile
Attorney for Applicants
Registration No. 24753
(248) 649-3333

YOUNG & BASILE, P.C.
3001 West Big Beaver Road
Suite 624
Troy, MI 48084-3107
ARB/jfz

RECEIVED
SEP 26 2002
TECHNOLOGY CENTER R3700



7/c

Our Reference: ITT-229-D

PATENT 9-2602
A. Cowan

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: David L. Noone, Frank L. Mitchell
and Peter Wenig

Serial No.: 09/995,213

Filing Date: November 26, 2001

Examiner/Group Art Unit: David L. Noone/3752

Title: MULTI-LAYER TUBING HAVING
ELECTROSTATIC DISSIPATION FOR
HANDLING HYDROCARBON FLUIDS

AMENDMENT

BOX NON-FEE AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

In response to the Office Action of June 19, 2002, please enter the following amendment in the above-identified matter.

If any charges or fees must be paid in connection with the following communication, they may be paid out of our Deposit Account 25-0115.

In the claims:

SubD11 35. (Amended) An elongated multi-layer tubing for connection to a motor vehicle system to contain and convey fluids containing hydrocarbons, the multi-layer tubing comprising:

C 1 a first layer disposed radially innermost the first layer having an inner face capable of prolonged exposure to fluids containing hydrocarbons and an outer face spaced a predetermined thickness from the inner surface, the first layer composed of an extrudable melt-processible thermoplastic material; and

at least one additional layer disposed radially outward of the first layer and in overlying relationship thereto, said at least one additional layer composed of an extrudable melt-processible thermoplastic material and connected to the first layer in an essentially permanent manner.

RECEIVED

SEP 26 2002
TECHNOLOGY CENTER R3700